

RUT140

INDUSTRIAL ETHERNET ROUTER

The RUT140 is a compact industrial Ethernet router, enhancing security through network isolation for end devices. Equipped with two Ethernet ports, DIN rail, and an industrial 3-pin connector, it ensures seamless connectivity and easy installation. The router comes with RutOS, Wi-Fi 4, and supports industrial protocols such as Modbus, DLMS, DNP3, and OPC UA, and is compatible with RMS for efficient remote and on-site management.



RUT140 360° VIEW



RUT140

Power: 9-30 V ~

Default IP: 192.168.1.1

CONNECTIVITY

2 x 10/100 Mbps Ethernet ports,
Wi-Fi 4

POWER INPUT

1 x 3-pin power connector
tailored for industrial use

EASY INSTALLATION

Simple installation with an
integrated DIN rail

RMS

Remote management,
access & VPN services



RMS COMPATIBLE WITH RUT140

MANAGEMENT | ALERTS | CONFIGURATION | ACCESS | FOTA

REMOTE
MANAGEMENT
SYSTEM

KEY FEATURES


HARDWARE

CPU	Mediatek, 580 MHz, MIPS 24KEc
Storage	16 MB serial NOR flash
Memory	128 MB, DDR2
Powering options	3-pos plugable terminal block, 9-30 VDC
Antenna connectors	1 x RP-SMA for Wi-Fi
Ethernet	2 x 10/100 Ethernet ports: 1 x WAN, 1 x LAN
WiFi	IEEE 802.11b/g/n, Access Point (AP), Station (STA)
Other	1 x Grounding screw
Status LEDs	1 x WAN type LED, 1 x LAN type LED, 1 x Power LED
Operating temperature	-40 °C to 75 °C
Housing	Aluminium housing with integrated din rail
Dimensions (W x H x D)	113.10 x 25 x 68.6 mm
Weight	142.3 g

SOFTWARE

Operating system	RutOS (OpenWrt based Linux OS)
Network protocols	TCP, UDP, IPv4, IPv6, ICMP, NTP, DNS, HTTP, HTTPS, SFTP, FTP, SMTP, SSL/TLS, ARP, VRRP, PPP, PPPoE, UPNP, SSH, DHCP, Telnet, SMPP, SNMP, MQTT, Wake On Lan (WOL)
VPN and tunneling	OpenVPN, IPsec, GRE, PPTP, L2TP, Stunnel, DMVPN, SSTP, ZeroTier, WireGuard, Tinc
Monitoring and Management	WEB UI, CLI, SSH, SMS, Call, Email, TR-069, SNMP, JSON-RPC, MQTT, RMS
Cloud solutions	RMS, FOTA, Azure IoT Hub, Cloud of Things, Cumulocity
Hotspot	Captive portal (Hotspot), internal/external Radius server, SMS authorization, internal/external landing page, walled garden, user scripts, URL parameters, user groups, individual user or group limitations, user management, 9 default customizable themes and option to upload and download customised hotspot themes

FRONT VIEW



BACK VIEW

